

CHLORIDE POWER PROTECTION

Desk Power from 300 to 650 VA



Uninterruptible Power Supply

The Range

Designed to increase the reliability and availability of workstations, point-of-sale systems and network equipment, Desk Power is available from 300 to 650 VA. This compact UPS uses off-line technology to provide a basic level of protection.

Flexibility

Desk Power can be positioned horizontally, vertically or wall-mounted. Reduced dimensions mean Desk Power is easily integrated into office environments with no disruption to customer premises. In addition, Desk Power offers additional data line protection facilitating communications and securing Internet and LAN connections.

Communication

Desk Power comes with a USB and RS232 communication port providing you with complete and easy interaction with your UPS. Desk Power is fully compatible with Chloride's connectivity suite.

Chloride's range of software solutions has everything you need to preserve data and maximise system uptime. Key features include:

- **Safe System Shutdown** - Preserve data integrity and minimize recovery delays with automated system shutdown. Chloride's software monitors the UPS for power failure, low battery or other events that jeopardize computer power and initiates controlled systems shutdown.
- **Safe Network Shutdown** - Multiple computers on a shared power source also need to share power status information to enable safe shutdown of all systems. Several architectures are available that deliver flexibility, simplicity and reliability in network-based shutdown.
- **Remote Messaging** - Chloride's software keeps you informed anywhere. Fault and recovery messages are sent via network, email, pager or SNMP trap.
- **Remote Management** - Site power and UPS status information can be accessed securely from any computer on your IP-based network. View event history and voltage logs for trend analysis. Consult your UPS system status in real time for situational decision support. Access is based on User Authentication with 128bit, MD5 encryption.

Applications

Desk Power provides secure power for a wide range of applications including:

- Office equipment and peripherals
- Individual PCs and workstations
- Network storage systems
- PBAX area
- Small servers

Secure Power Always

Supplying you with a UPS alone will never deliver the level of business continuity you require. Chloride offers a range of maintenance plans which will:

- Help deliver reliability to your load
- Extend the life of your power protection equipment
- Optimize your capital expenditure
- Provide risk management at a fixed cost
- Help to control your business environment
- Provide a pro-active approach to disaster recovery

Contact your local Chloride sales office for more information.

Delegate your power management to the experts.

Type	DESK POWER 300	DESK POWER 500	DESK POWER 650		
ELECTRICAL DATA					
Power (VA/W)	300/180	500/300	650/390		
Input	Voltage	230V			
	Voltage window	180-280V			
	Input protection	10 A circuit breaker			
	Frequency	50/60 Hz			
	Power Factor	0.6			
Battery	Type	Maintenance-free lead			
	Typical autonomy (min)	10	10	10	
	Voltage	12V	12V	12V	
Output	Voltage	230V			
	Voltage Tolerance	Line mode	less than 1V with respect to input		
		Battery mode	230V ± 10%		
		Frequency	same as input frequency		
	Line mode	50/60Hz ± 1Hz			
		Battery mode	50/60Hz ± 1Hz		
	Admissible overloads	120% nominal load, 4 minutes			
		150% nominal load, 10 seconds			
	GENERAL DATA				
	Safety	EN50091-1-1 (CE)			
RFI emission	EN50091-2, Class B				
Immunity	IEC 1000-4-2/3/4/5, Level 3				
Efficiency	Line mode	>95%			
	Battery mode	>70%			
Ambient working temperature	0°C- 40°C				
Ambient storage temperature	-15°C-50°C				
Relative humidity allowed	0-95% without condensation				
MECHANICAL DATA					
UPS	Weight (kg)	2.5	3.2	3.9	
	Dimensions (mm)	Width	60	60	75
		Height	190	190	190
		Depth	230	230	230
		Weight (kg)	3.0	3.7	4.4
Packaging	Dimensions (mm)	Width	140	140	140
		Height	275	275	275
		Depth	370	370	370
		Indicators	LED on front panel, acoustic alarm		
CONNECTIONS					
Input	1 socket IEC320-C14				
Output (UPS protection)	2 sockets IEC320-C13	3 sockets IEC320-C13			
Output (Surge protection)	1 socket IEC320-C13	1 socket IEC320-C13			
Line filter	Yes				
Communication port	SUB-D 9 pin and USB connection				

Chloride UPS Systems
WORLD HEADQUARTERS
 Via Fornace 30
 40023 Castel Guelfo (BO)
 Italy
 Tél. : +39 0542 632 111
 Fax : +39 0542 632 120
 enquiries@chloridepower.com

Closest Chloride Contact in UK:
Chloride Power Protection
 George Curl Way
 Southampton, Hampshire, SO18 2RY
 United Kingdom
 Telephone: +44 (0) 23 8061 0311
 Facsimile: +44 (0) 23 8061 0852
 Uk.enquiries@chloridepower.com
www.chloridepower.com/uk

Closest Chloride Contact in Australia:
Chloride Power Protection
 Ground Floor
 16 Giffnock St, North Ryde, NSW 2113
 Australia
 Telephone: +61 2 9888 1266
 Facsimile: +61 2 9888 1966
 Australia.sales@chloridepower.com
www.chloridepower.com/au

For full list of contacts in other countries please visit our website at www.chloridepower.com



GOST certification

PRODUCT SERVICE

Certificate No. EMS 76732

Certificate No. FM 11043